



2.3 BISCUIT CRUSING MACHINE



- Biscuit Crushing Machines are horizontal.
- Biscuits into the Horizontal Biscuit Crushing Machine are manually dropped into the machine inlet chamber.
- Horizontal Biscuit Crushing Machine has 2 apparatus and is suitable for manual and automated use.
- Existing Biscuits will be manually dropped into the appropriate Shredding Hopper on the Machine.
- HORIZONTAL Machine automatically breaks (pieces) on the Biscuit Crusher unit, which is supplied automatically
- The separation process is 2 Kinds of Separation Units and the products are divided into 3 or 4 groups.
- More detailed information about the separation units can be found in a separate relevant brochure.
- Biscuit Crushing Machine is ideal for confectionery, cake and ice cream producers.

MACHINE MODEL	PRODUCTION CAPACITY	FEEDING TYPE	MAIN PRODUCT DIMENSIONS	BISCUIT THICKNESS
PBKM-PAS-Y500-KIR-3-5 EL2000	150-250 Kg/H	Manuel	3-5 mm	3-8 mm
PKM-PAS-Y500-5-8 EL2000	200-350 Kg/H	Manuel	4-8 mm	3-8 mm
PKM-PAS-Y500-8-12 EL2000	300-450 Kg/H	Manuel	8-12 mm	3-8 mm

ELECTRILAC POWER	MAIN MACHINE POWER - 2.5 kW
VOLTAGE	400 V , 3 PHASE, 50 Hz
CONTROL PANEL VOLTAGE	220 VAC
WEIGHT	450 kg
COLOR	STAINLESS STEEL
MEASURES	WIDTH: 1150 mm X LENGTH 1600 mm X HEIGHT 1500 mm
ADDITIONAL OPTIONS	WHEELS OR ADJUSTABLE FEET
SEPARATION UNIT	AUTOMATICAL VIBRATORY SEPARATION SYSTEM

MACHINE PBKM-PAS-Y500-KIR-3-5 EL2000


PRODUCT SIZE	0-3 mm	3-5 mm	X > 5 mm
TOTAL PRODUCT RATIO	10-20%	70-80%	5-10%

MACHINE 2- PBKM-PAS-Y500-5-8 EL2000

PRODUCT SIZE	0-4mm	4-8 mm	X > 8 mm
TOTAL PRODUCT RATIO	10-20%	70-80%	5-10%

MACHINE 3- PBKM-PAS-Y500-8-12 EL2000

PRODUCT SIZE	0-8 mm	8-12mm	X > 12 mm
TOTAL PRODUCT RATIO	%10-20	%70-80	%5-10



- All Values are based on optimum temperature, hardness and Biscuit Recipe compositions.
- On request, testing and a more accurate calculation of productivity are carried out, depending on the specifics of the client's production.